



# DCU 151+ Welfare

## Mobile Decontamination Units

The DCU 151+ Welfare is a variant of the most popular unit in the SMH DCU Range. It is compact at only 4.6m in length and with a single shower it is suitable for up to four workers. The 151+ Welfare variant includes spacious welfare and toilet facilities. The unit can be fully self-contained when the fresh water tank is used in conjunction with the on-board LPG generator.

SMH has been a leading manufacturer of decontamination units for over 30 years. SMH DCU's provide mobile decontamination facilities for workers operating in environments where airborne contaminants are a potential risk but a permanent decontamination facility is impractical, such as in demolition and remediation work or emergency situations. The units are also suitable for a range of industries and different hazardous materials.

The DCU exceeds the requirements of *HSG247 Asbestos: The licensed contractors' guide*, and the HSE's *Control of Asbestos Regulations 2012 Approved Code of Practice, Regulation 23*.



- 4 Decon. Capacity
- 1 Showers (No. of)
- 1 Toilets (No. of)
- 2 Welfare (Seating)
- Fuel: Gas
- Fuel: Electric (Option)

### At a glance

- Designed and built to exceed the requirements of the UK's asbestos removal regulations;
- Three-stage decontamination arrangement consisting of a clean, shower and dirty zone;
- Self-closing doors maintain the integrity of the decontamination process;
- Manufactured from smooth moulded GRP, the units are waterproof and easily cleaned after use;
- Easy to maintain with external access to generator, water pump, waste water filter system and gas bottle.

**Available to buy or hire – contact your nearest branch**

Leeds  
0113 279 9003  
leeds@smhproducts.com

London  
0127 781 0035  
london@smhproducts.com

Bristol  
0117 403 5830  
bristol@smhproducts.com

Glasgow  
0141 556 6600  
glasgow@smhproducts.com

Romsey  
0179 452 4000  
romsey@smhproducts.com

St Helens  
0174 426 660  
sthelens@smhproducts.com

Washington  
0191 456 6002  
washington@smhproducts.com

Birmingham  
0121 328 6000  
birmingham@smhproducts.com

# Technical Data

## Specifications

Overview	Capacity	4
	Stages	3
	Showers	1
	Toilets	1
	Welfare: Capacity	2
	Welfare: Fridge	✓
	Welfare: Microwave	✓
Power & Services	Fuel: Gas	✓
	Fuel: Dual	Optional
	Generator, Max. Output	3.5kVA
	LPG Gas Bottle, Max.	2x 19kg Propane
	Power Supply, Voltage-Frequency	230V-50Hz
	Socket Config.: Gas	1x 16A
	Socket Config.: Dual Fuel	1x 16A, 1x 32A
	Water Tank: Fill Method	Internal/Mains
	Shower Pump	1x 24V, 3 bar, up to 12LPM
	Waste Pump	1x 24V, 3 bar, up to 18LPM
	Waste Filters Size	5µm
	Electric Heating	1x 400W, 2x 60W
	Negative Pressure Unit (NPU)	Decon 300
Chassis & Weights	Axles	1
	Weight, Unladen kg	950
	Weight, Max. Load kg	1300
	Wheels & Tyres	175 R 13C
	Spare Wheel & Carrier	Optional
Dimensions	Battery Powered Tracker	Optional
	External Length mm	4632
	External Width mm	1844
	External Height mm	2800
	Internal Length mm	3200
	Internal Width mm	1750
	Internal Height mm	2000

## Features

- Trailer-based mobile decontamination unit
- Compact yet powerful Negative Pressure Unit (NPU)
- LPG propane gas generator with fully contained compartment and gas bottle storage locker
- Room sealed water heater with electronic start and low NOx emissions
- Extra low voltage, energy saving IP67 PIR LED lighting
- Lockers with sockets for recharging powered respirators
- Space heating for all-year round use
- Easy-to-clean glass-reinforced plastic (GRP) internals
- Boiler-fed showers are standard; electric optional
- Toilet facilities, including a sink, hot water, mirror, soap dispenser and cassette toilet
- Welfare facilities, including seating, a worktop, sink, fridge and microwave

## Certification

- All units comply with BS EN 7671:2018 Requirements for electrical installations; BS EN 6767-2:1998 Transportable accommodation units; BS EN 1949:2011+A1:2013 Specification for the installation of LPG systems for habitation purposes;
- All units are supplied with an electrical installation certificate issued by a qualified electrician and all gas appliances are fitted, tested and certified to conform to current Gas Safety Installation Use Regulations 1994;
- All NPU's in the units are PAT and DOP tested;
- All NPU's comply with BS EN 8520-2:2009 Equipment used in the controlled removal of asbestos-containing materials (ACMs);
- All HEPA filters comply with BS EN 1822-1;
- All appliances comply with BS EN 60335-2-69 Household and similar appliances;
- The units are manufactured at an ISO 9001 quality assured site;
- The vehicle conforms to Whole Type Vehicle Approval for Vehicle Category SA02.

## Optional Extras & Accessories

### Battery Powered Tracker

- Stolen unit recovery product
- Self-powered with up to 5 years standby
- Uses VHF technology
- Traceable in containers, lock-ups or underground car parks
- Only tracker system supported by UK Police forces nationwide
- One-time use operation



### Spare Wheel & Carrier

- Mounted under the trailer, to the rear of the chassis

